

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Trade name **PERFO GRIF**

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the product

**LIQUID ACID  
DISINFECTION OF MILKING CLUSTER**

##### 1.3. Details of the supplier of the safety data sheet

Company identification

**HYPRED SAS  
55, Boulevard Jules Verger B.P 10180  
35803 DINARD Cedex - FRANCE  
Tél : +33 (0)2 99 16 50 00  
Fax : +33 (0)2 99 16 50 20  
e-mail : kersia@kersia-group.com**

For information regarding this safety data sheet, please contact :  
regulatory@kersia-group.com

##### 1.4. Emergency telephone number

Emergency phone number

**Emergency direct number ( 24 hours a day, 7 days a week ) : (+)1-760-476-3961  
Access code : 333021**

**DUBLIN (Information available at the Poisons Information  
Centre - Beaumont Hospital)  
+353 (01) 809 2566 (24 hour service)**

**LONDON (Information available at the National Poison Unit -  
Guy's Hospital)**

## PERFO GRIF

Code: 0 322 S

### Material Safety Data Sheet compliant with Regulation (EC) 2015/830

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture meets the classification criteria provided for under Regulation (EC) No 1272/2008.

Skin corrosion - Category 1B	H314: Causes severe skin burns and eye damage.
Organic peroxide Typ G	
Substance corrosive to metals - Category 1	H290: May be corrosive to metals.
Specific target organ toxicity (STOT) - single exposure - Category 3	H335: May cause respiratory irritation.
Hazardous to the aquatic environment — Chronic - Category 1	H410: Very toxic to aquatic life with long lasting effects.
Acute toxicity - Category 4 (per dermal route)	H312: Harmful in contact with skin.
Serious damage to eyes - Category 1	H318: Causes serious eye damage.

### 2.2. Label elements

#### Labelling according to 1272/2008/EC Regulation:

##### Hazard pictograms(s) :



##### Signal word :

Danger

Contains : acetic acid+ Peracetic acid+ Hydrogen peroxide

##### Hazard statement(s) :

H290: May be corrosive to metals.

H312: Harmful in contact with skin.

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

---

H314: Causes severe skin burns and eye damage.  
H335: May cause respiratory irritation.  
H410: Very toxic to aquatic life with long lasting effects.

#### **Precautionary statement(s) :**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260: Do not breathe vapours/spray.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER or doctor/physician.  
P391: Collect spillage.  
P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

#### **2.3. Other hazards**

Risk of breaking down in contact with metals, bases, reducing agents or flammable materials.  
Danger of breaking down under the action of warming or heat.

### **SECTION 3: Composition/information on ingredients**

#### **3.1. Substances**

Not applicable as this involves a mixture.

#### **3.2. Mixtures**

Chemical nature of the mixture : LIQUID ACID

## PERFO GRIF

Code: 0 322 S

### Material Safety Data Sheet compliant with Regulation (EC) 2015/830

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

Substance(s)	CAS number(s)	EINECS number(s)	No registration REACH	Classification according to Regulation 1272/2008/EC	Type
10% <= acetic acid < 25%	64-19-7	200-580-7	01-2119475328-30	Flam. Liq. 3 H226 Skin Corr. 1A H314	(1)
8% <= Hydrogen peroxide < 35%	7722-84-1	231-765-0	Biocidal active substance, regarded as already registered	Ox. Liq. 1 H271 Acute Tox. 4 (inhalation) H332 Acute Tox. 4 (oral) H302 Skin Corr. 1A H314 STOT SE 3 H335 Aquatic Chronic 3 H412 Eye Dam. 1 H318	(1)
5% <= Peracetic acid < 10%	79-21-0	201-186-8	Biocidal active substance, regarded as already registered	Flam. Liq. 3 H226 Org. Perox. D H242 Acute Tox. 4 (inhalation) H332 Acute Tox. 4 (dermal) H312 Acute Tox. 4 (oral) H302 Skin Corr. 1A H314 Aquatic Acute 1 H400 STOT SE 3 H335 Aquatic Chronic 1 H410 M Factor (Acute) 1 M Factor (Chronic) 10	(1)

#### Type

- (1) : Substance classified as hazardous for health and/or the environment
- (2) : Substance with an exposure limit at the work station.
- Substance of very high concern candidate for the authorisation procedure:
- (3) : Substance considered as PBT (persistent, bioaccumulable, toxic)
- (4) : Substance considered as vPvB (very persistent, very bioaccumulable)
- (5) : Substance considered as carcinogenic category 1A
- (6) : Substance considered as carcinogenic category 1B
- (7) : Substance considered as mutagenic category 1A
- (8) : Substance considered as mutagenic category 1B
- (9) : Substance considered as reprotoxic category 1A
- (10) : Substance considered as reprotoxic category 1B
- (11) : Substance considered as endocrine disrupter

Full text of H- and EUH- phrases : see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General indications:

Take the contaminated clothes and shoes off immediately. Wash them before wearing them again.  
In case of faintness , get medical advice/attention. Show this safety data sheet to the doctor.

#### In the event of inhalation :

Bring to fresh air.  
Put into practice respiratory help procedure if needed and get medical advice immediately.

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

---

#### **In the event of contact with the skin :**

Take off immediately all contaminated clothing.  
Wash immediately with plenty of water for 15 minutes at least.  
Immediately call a POISON CENTER or doctor/physician.

#### **In the event of contact with the eyes :**

Rinse at once with a soft stream of water for at least 15 minutes, eyes wide open.  
Remove contact lenses if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER or doctor/physician.

#### **In the event of ingestion :**

Rinse mouth.  
Do NOT induce vomiting.  
Send to hospital.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact :** Corrosive : Causes severe burns.  
Harmful in contact with skin.

**Eye contact :** Causes serious eye damage.

**Ingestion :** Causes severe burns in mouth and digestive tract.

**Inhalation :** May cause respiratory irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Treatments :** Symptomatic treatment

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### **Suitable extinguishing media :**

Waterspray.  
Foam, powder, carbon dioxide.  
Agents compatible with other products involved into fire.

#### **Unsuitable extinguishing media :**

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

Organic compounds

#### 5.2. Special hazards arising from the substance or mixture

Thermal decomposition gives Oxygen, that can enhance sites of combustion.

#### 5.3. Advice for firefighters

Wear independent respiratory equipment and protective suit.  
Collect contaminated firefighting water separately, must not be discharged into the drains.  
Keep containers cool by spraying with water if exposed to fire.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel :

Evacuate non-essential staff and those not equipped with individual protection apparatus.

##### 6.1.2. For emergency responders :

Evacuate the personnel to a safe location.  
Keep people upwind and away from the location of the flow/leak.  
Use personal protection equipment.

#### 6.2. Environmental precautions

Intervention limited to trained staff.  
Do not discharge the product directly to sewer or to environment.  
Take as soon as possible all incompatible materials away.

#### 6.3. Methods and material for containment and cleaning up

##### Small spillage :

Pump in a reservoir of help.

##### Large spillage :

Mark out, soak up with an inert absorbant and pump in an emergency tank.  
Do not use: textiles, sawdust, flammable substances.  
Never return spills in original containers for re-use.  
Keep in suitable, properly labelled and closed containers for disposal.

#### 6.4. Reference to other sections

Respect protective measures presented at heading 8.  
Refer to section 13 for the elimination.

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Avoid contact with skin, eyes and clothing.
- Do not inhale vapour, aerosols, mist.
- Do not eat, drink or smoke in work area. Avoid projections during use.
- Take off immediately all contaminated clothing.
- Keep away from incompatible matters (see heading 10).

### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1. Storage :

- Keep only in the original container.
- Keep in a clean, cool and well-ventilated place away from sources of heat and intense light.
- Keep away from incompatible matters (see heading 10).
- Keep container closed.

#### 7.2.2. Packaging or wrapping materials :

- High density polyethylene recommended.

### 7.3. Specific end use(s)

- PERFO GRIF is for use as a biocide.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure limit values :**

**PERFO GRIF**

Code: 0 322 S

*Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

Substance	Country	Type	Value	Unit	Comments	source		
Peracetic acid	FRA	VLCT Short term	1,58	mg/m3	Valeur proposée par l'INRS		INRS	
			0,5	ppm	Valeur proposée par l'INRS		INRS	
		VLEP 8h	0,63	mg/m3	Valeur proposée par l'INRS		INRS	
			0,2	ppm	Valeur proposée par l'INRS		INRS	
acetic acid	EU	OEL 8h	10	ppm		International limit values for chemical agents		
			25	mg/m <sup>3</sup>		International limit values for chemical agents		
Hydrogen peroxide	FRA	VLEP 8h	1	ppm	Valeur limite indicative	International limit values for chemical agents		
			1,5	mg/m <sup>3</sup>	Valeur limite indicative	International limit values for chemical agents		
		EMV (Exposure medium value) :	1	ppm				
			1,5	mg/m3				
	AUT	OEL 8h	1	ppm		International limit values for chemical agents		
			1,4	mg/m <sup>3</sup>		International limit values for chemical agents		
		OEL Short term	2	ppm		International limit values for chemical agents		
			2,8	mg/m <sup>3</sup>		International limit values for chemical agents		
	BEL	OEL 8h	1	ppm		International limit values for chemical agents		
			1,4	mg/m <sup>3</sup>		International limit values for chemical agents		
	CHE	OEL 8h	0,5	ppm		International limit values for chemical agents		
			0,71	mg/m <sup>3</sup>		International limit values for chemical agents		
		OEL Short term	0,5	ppm		International limit values for chemical agents		
			0,71	mg/m <sup>3</sup>		International limit values for chemical agents		
	DEU	OEL 8h	0,5	ppm		International limit values for chemical agents (German Research Foundation)		
			0,71	mg/m <sup>3</sup>		International limit values for chemical agents (German Research Foundation)		
		OEL Short term	0,5	ppm		International limit values for chemical agents (German Research Foundation)		
			0,71	mg/m <sup>3</sup>		International limit values for chemical agents (German Research Foundation)		
	DNK	OEL 8h	1	ppm		International limit values for chemical agents		
			1,4	mg/m <sup>3</sup>		International limit values for chemical agents		
		OEL Short term	2	ppm		International limit values for chemical agents		
			2,8	mg/m <sup>3</sup>		International limit values for chemical agents		
	ESP	OEL 8h	1	ppm		International limit values for chemical agents		
			1,4	mg/m <sup>3</sup>		International limit values for chemical agents		
GBR	OEL 8h	1	ppm		International limit values for chemical agents			
		1,4	mg/m <sup>3</sup>		International limit values for chemical agents			
	OEL Short term	2	ppm		International limit values for chemical agents			
		2,8	mg/m <sup>3</sup>		International limit values for chemical agents			
STEL		2	ppm		MSDS supplier			



## PERFO GRIF

Code: 0 322 S

### Material Safety Data Sheet compliant with Regulation (EC) 2015/830

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

Hydrogen peroxide	GBR	STEL	2,8	mg/m <sup>3</sup>	MSDS supplier
		TWA	1	ppm	MSDS supplier
	1,4		mg/m <sup>3</sup>	MSDS supplier	
	SWE	OEL 8h	1	ppm	International limit values for chemical agents
			1,4	mg/m <sup>3</sup>	International limit values for chemical agents
	EST	VLCT Short term	2	ppm	Regulation No 293 of the Government of the Republic of Estonia
			3	mg/m <sup>3</sup>	Regulation No 293 of the Government of the Republic of Estonia
		VLEP 8h	1	ppm	Regulation No 293 of the Government of the Republic of Estonia
			1,4	mg/m <sup>3</sup>	Regulation No 293 of the Government of the Republic of Estonia
	HRV	OEL 8h	1	ppm	
			1,4	mg/m <sup>3</sup>	
		OEL 15 min	2	ppm	
2,8			mg/m <sup>3</sup>		

## 8.2. Exposure controls

According to the requirements of Directive 98/24 /EC, the employer is required to conduct a risk assessment and implement appropriate risks management measures.

\* For any situation where the absence of risk is not proven, he must consider the substitution or reduction of risk by improving in priority processes used and collective protection measures. The effectiveness of the solutions implemented will be checked by measurement in comparison to the statutory limit values for substances defined in Section 8.1.

\* If the risk remains after these corrective actions, he must always check by routinely measuring compliance with regulatory OEL if they exist in section 8.1 and apply all the individual protective measures given in section 8.2.

\* When formalized risk assessment indicates a low risk to workers' health, control of compliance with regulatory OEL may not be considered and all individual protection measures is not always mandatory.

### 8.2.1. Appropriate engineering controls :

Ensure adequate ventilation.

Apply the necessary technical measures to comply with the professional exposure limit values.

### 8.2.2. Individual protection measures, such as personal protective equipment :

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

---

#### **Eye/face protection :**

Use safety glasses or facial screen in conformity with the EN 166 standard.



#### **Hand protection :**

Use chemical resistant gloves approved to EN 374.

Examples of preferred materials for insulating gloves:

PVC

Neoprene.

Butyl rubber.



#### **Skin protection :**

Wear boots and a protective cloth with chemical resistance.



#### **Respiratory protection :**

At the time of handling leading to vapor formation, wear a half-mask in compliance with the European standard EN 140 or a complete mask with a filter in conformity with the European standard EN 136 (in conformity with the European standard EN 141 or EN 14387) of type:

ABEK.

At the time of applications by spraying (leading to aerosols), wear a half-mask in compliance with the European standard EN 140 or a complete mask in conformity with the European standard EN 136 equipped with a filter (in conformity with the European standard EN 143) of the following type:

P: Particles, solid aerosols and liquids.

It is possible to combine the anti-vapor filters and anti-aerosols.



#### **Thermal hazards :**

Not applicable

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

#### Health measures :

Safety shower and eye wash fountain near to workplace.  
After using, wash systematically all personal protective equipment.  
Handle in accordance with good industrial hygiene practices and the safety instructions.

#### 8.2.3. Environmental exposure controls :

Do not discharge the product directly to sewer or to environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Clear liquid
Colour	Colourless
Odour	Pungent
Odour threshold	Not available
Pure pH	0.9±0.3
pH value at 10g/l	3±0.5
Freezing point :	-25 °C
Boiling point (OECD : 103)	100.4 °C
Flash point (EC : A9)	> 110 °C
Evaporation rate:	Not available
Flammability	The mix is not considered be flammable according to the criteria of Regulation 1272/2008/EC.
Vapour pressure	Not available
Vapour density	Not available
Mass density	1.09±0.01 g/cm <sup>3</sup>
Relative density	1.09±0.01
Solubility in water	Soluble in water in all proportions
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
	>= 60 °C (Self-accelerated decomposition temperature)
Viscosity	Not available
Explosive properties	Not applicable
Oxidising properties (UN : 0.2)	non-oxidising

### 9.2. Other information

No additional information.

## SECTION 10: Stability and reactivity

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

#### 10.1. Reactivity

Danger of breaking down under the action of warming or heat.

#### 10.2. Chemical stability

Stable in the recommended storage and handling conditions.

#### 10.3. Possibility of hazardous reactions

Avoid the contact with the basis, metals, reducing agents, organic and inflammable matters.

#### 10.4. Conditions to avoid

Light, heat.

#### 10.5. Incompatible materials

Basis.  
Organic matters.  
Metals.  
Flammable substances.  
Reducing agents.

#### 10.6. Hazardous decomposition products

Release of oxygen.

These data are given for the concentrated mixture. The use of the mixture under its diluted form must be performed in conformity with data given by the technical data sheet and the technical adviser.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### **Substance-related data:**

##### Acute toxicity

Hydrogen peroxide ( 35% ) : LD 50 - oral rat 1,193 - 1,270 mg/kg. - MSDS supplier  
Hydrogen peroxide ( 35% ) : LD 50 - dermal rabbit > 2,000 mg/kg. - MSDS supplier  
Hydrogen peroxide ( 100% ) : LC 50 - inhalation - 4h rat 1.5 mg/L. - Mists - MSDS supplier  
acetic acid ( 74% ) : LD 50 - oral rat 3,310 mg/kg. - MSDS supplier  
acetic acid ( 74% ) : LC 50 - inhalation - 4h rat > 16,000 ppm. - MSDS supplier

##### Skin corrosion/irritation

Hydrogen peroxide ( 35% ) : Skin irritation rabbit . Irritating - MSDS supplier  
acetic acid ( 74% ) : Cutaneous contact . Corrosive. - MSDS supplier

Serious damage to eyes/eye irritation

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

---

Hydrogen peroxide ( 10% ) : Eye irritation . Serious damage to eyes - MSDS supplier  
acetic acid ( 74% ) : Eye contact : . Corrosive. - MSDS supplier

#### Sensitisation

acetic acid ( 74% ) : Sensitisation . Not sensitising - MSDS supplier  
Hydrogen peroxide ( 35% ) : Sensitisation guinea-pig . Not sensitising - MSDS supplier

#### Mutagenicity

Hydrogen peroxide ( 35% ) : in vivo . Not mutagenic - MSDS supplier

#### Carcinogenicity

Hydrogen peroxide ( 35% ) : Dermal route mouse . Not carcinogenic - MSDS supplier

#### Specific target organ toxicity - single exposure

Hydrogen peroxide ( 50% ) : DR 50 mouse 665 mg/m<sup>3</sup>. Irritating to respiratory system. - MSDS supplier

### **Mix-related data: :**

#### Acute toxicity

LD 50 - oral rat (Sprague-Dawley) (OECD 420): > 2,000 mg/kg.

#### Skin corrosion/irritation

Skin corrosivity . The mixture should be considered as corrosive because of its extreme pH.

#### Serious damage to eyes/eye irritation

Ocular corrosivity . Causes serious eye damage according to the criteria of Regulation 1272/2008/EC.

#### Respiratory / skin sensitisation

Skin sensitisation (OECD 406): . Not sensitising

Respiratory sensitisation . The mixture is not considered as a respiratory sensitizer according to 1272/2008/EC Regulation.

#### Repeated dose toxicity

NOAEL - oral rat (Sprague-Dawley) (OECD 408): 23.4 mg/kg bw day.

#### Mutagenicity

(OECD 471, 473, 474): . Not mutagenic

#### Carcinogenicity

. The classification criteria are not met given the available data.

#### Reproductive toxicity

. The classification criteria are not met given the available data.

#### Specific target organ toxicity - single exposure

Respiratory tracts irritation . May cause respiratory irritation.

#### Specific target organ toxicity - repeated exposure

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

. The classification criteria are not met given the available data.

Aspiration hazard

. The classification criteria are not met given the available data.

#### **Most important symptoms and effects, both acute and delayed :**

**Skin contact :** Corrosive : Causes severe burns.

Harmful in contact with skin.

**Eye contact :** Causes serious eye damage.

**Ingestion :** Causes severe burns in mouth and digestive tract.

**Inhalation :** May cause respiratory irritation.

## **SECTION 12: Ecological information**

### **12.1. à 12.4. Toxicity - Persistence and degradability - Bioaccumulative potential - Mobility in soil**

#### **Substance-related data:**

Acute toxicity

Hydrogen peroxide ( 35% ) : NOEC - 96h fishes (Pimephales promelas) 4.3 mg/L. - MSDS supplier

Hydrogen peroxide ( 35% ) : EC 50 - 48h shellfishes (Daphnia pulex) 2.4 mg/L. - MSDS supplier

Hydrogen peroxide ( 35% ) : NOEC - 48h shellfishes (Daphnia pulex) 1 mg/L. - MSDS supplier

Hydrogen peroxide ( 35% ) : EC 50 - 72h algae (Skeletonema costatum) 2.6 mg/L. - MSDS supplier

acetic acid ( 74% ) : LC 50 - 96 fishes > 300.82 mg/L. - MSDS supplier

acetic acid ( 74% ) : LC 50 - 48h daphnia > 300.82 mg/L. - MSDS supplier

acetic acid ( 74% ) : EC 50 - 72h algae > 300.82 mg/L.

Hydrogen peroxide : NOEC - 72h algae 0.63 mg/L. - MSDS supplier

Degradability

Hydrogen peroxide ( 35% ) : Aerobic biodegradability, half time - 0,3-5days . Easily biodegradable. - MSDS supplier

acetic acid ( 74% ) : Biodegradability . Biodegradable - MSDS supplier

Bioaccumulation

Hydrogen peroxide ( 35% ) : Log Pow - 1.57 . Not bioaccumulative - MSDS supplier

#### **Mix-related data :**

Acute toxicity

LC 50 - 96h fishes (Oncorhynchus mykiss) (OECD 203): 10.1 mg/L.

EC 50 - 48h daphnia (Daphnia magna) (OECD 202): 37.3 mg/L.

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

EC 50 - 72h algae (Scenedesmus subspicatus) (OECD 201): 30.5 mg/L.

#### CHRONIC TOXICITY

. No data available.

#### Degradability

. Not applicable due to the rapid degradation of peracetic acid and hydrogen peroxide in the environment.

#### Bioaccumulation

. Not applicable due to the rapid degradation of peracetic acid and hydrogen peroxide in the environment.

#### Mobility

. Not applicable due to the rapid degradation of peracetic acid and hydrogen peroxide in the environment.

#### Conclusion :

The mixture is considered to be dangerous for the environment according to 1272/2008/EC Regulation.

#### 12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB

#### 12.6. Other adverse effects

No additional information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Treatment of the mixture :**

Do not discharge the product directly to sewer or to environment.

Comply with Directive 2008/98/EC of 19/11/2008 amended, relating to waste and to Decision 2000/532/EC (amended ultimately by Decision 2014/955/EC) that establishes a list of hazardous waste that must be taken to an approved centre.

##### **Packaging treatment :**

Rinse thoroughly the packaging with water and treat the effluent like wastes.

Comply with Directive 2008/98/EC of 19/11/2008 amended, relating to waste and to Decision 2000/532/EC (amended ultimately by Decision 2014/955/EC) that establishes a list of hazardous waste that must be taken to an approved centre.

### SECTION 14: Transport information

## PERFO GRIF

Code: 0 322 S

### Material Safety Data Sheet compliant with Regulation (EC) 2015/830

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

#### **ROAD TRANSPORT:**

Rail/Route (RID/ADR)

UN no : 3265

UN proper shipping name :CORROSIVE LIQUID, ACIDIC ORGANIC, N.O.S. (Peracetic acid+acetic acid+Hydrogen peroxide)

Transport hazard class(es) : 8

Packing group : II

Hazard code : 80

Label : 8



Tunnel code : E

Environmental hazard : Yes (Peracetic acid)

Special precautions for user : No information.

Limited Quantity (QL): 1L


#### **MARITIME TRANSPORT :**

IMDG

UN no :3265

UN proper shipping name : CORROSIVE LIQUID, ACIDIC ORGANIC, N.O.S. (Peracetic acid+acetic acid+Hydrogen peroxide)

Transport hazard class(es) : 8



Packing group : II

Marine pollutant : Yes (Peracetic acid)

Special precautions for user : No information.

EmS number : F-A,S-B

Limited Quantity (QL): 1L

**Transport in bulk according to Annex II of MARPOL and the IBC Code :**

Not concerned



## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

Version 6.0.0

Revision: 09/02/17

Print Date : 05/04/19

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Regulations relating to the hazards from major accidents :**

SEVESO 3 Directive (2012/18/EC) : E1

**Regulations relating to the classification, packing and labelling of substances and mixes :**

Regulation 1272/2008/EC amended.

**Waste regulations :**

2008/98/EC Directive amended by 2015/1127/EC Directive - Regulation 1357/2014/EC  
Decision 2014/955/EC which establishes the list of hazardous waste.

**Protection of workers :**

Directive 98/24/EC of 07/04/1998 on the protection of the health and safety of workers from the risks related to chemical agents at work.

**Regulation 850/2004/EC on persistent organic pollutants and modifying Directive 79/117/EC :** Not applicable

**Regulation 1005/2009/EC amended on substances that deplete the ozone layer :** Not applicable

**Regulation (EC) 648/2004 :**

Not concerned

Comply with national and local legislation.

#### 15.2. Chemical safety assessment

No

#### SECTION 16: Other information

The safety data sheet is additional to the technical data sheet but does not replace it. The information given here in is to the best of our knowledge correct and is given in good faith. We must also draw the user's attention on potential risks of the product is used for other purposes for which the product is known.

In no way does it exempt users from being aware of and complying with regulations applicable to their activity. It is their sole responsibility to take all necessary precautions in accordance to the usage of the product they are aware of.

Regulations are only stated in order to help users fulfill the duties involved in the use of the product.

## PERFO GRIF

Code: 0 322 S

### *Material Safety Data Sheet compliant with Regulation (EC) 2015/830*

**Version** 6.0.0

**Revision:** 09/02/17

**Print Date :** 05/04/19

---

This description should not be considered as exhaustive. It does not exempt users from ensuring if other demands need to be complied with-according to other laws than the ones hereby stated and applicable to holding and usage of the product-demands for which they will remain sole responsibility.

#### **Section(s) modified compared with the previous version :**

Revision of the safety data sheet according to 2015/830/EC Regulation.

#### **List of H phrases referred to in sections 2 and 3 :**

- H226 : Flammable liquid and vapour.
- H242 : Heating may cause a fire.
- H271 : May cause fire or explosion; strong oxidiser.
- H302 : Harmful if swallowed.
- H312 : Harmful in contact with skin.
- H314 : Causes severe skin burns and eye damage.
- H318 : Causes serious eye damage.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.
- H412 : Harmful to aquatic life with long lasting effects.

#### **Sources of key data used to compile the data sheet :**

INRS  
MSDS supplier  
International limit values for chemical agents

Regulation No 293 of the Government of the Republic of Estonia

#### **Historical :**

Version 6.0.0  
Cancels and replaces previous version 5.2.3